NEC/MITSUBISHI
NEC-MITSUBISHI ELECTRONICS DISPLAY

NEC MultiSync® LCD2060NX

- Professional LCD monitor with digital MVA TFT display
- Slim bezel design (17,5 mm)
- Stable and excellent picture quality with NTAA (Non-Touch-Auto-Adjustment)
- ErgoDesign®: Height adjustable stand [75 mm]
- Cable Management
- Low power consumption for reduced Total Cost of Ownership (TCO)
- Safety of investment with analog/digital interface
- Rapid Response Technology (25 ms)
- Versatile installation (VESA standard)
- Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2 ; Pixel Failure Class II

see more.

NEC MultiSync® LCD2060NX

Panel Technology	MVA TFT
Screen Size [inch/cm]	20.1/51
Viewing Angle	170° horizontal / 170° vertical (typ. at contrast ratio 10:1)
Contrast Ratio (typ.)	600:1
Brightness (typ.) [cd/m^2]	250
Response Time (typ.) [msec]	25 (10 white / black; 15 black / white)
Colours [million]	16.77
Horizontal Frequency [kHz]	31.5-91.1
Vertical Frequency [Hz]	56,0-85,0
Optimum Resolution	1600 x 1200 at 60 Hz
Other Resolutions	1280 x 1024; 1280 x 960; 1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 640 x 480; 720 x 400; 720 x 350;
Connectors	Digital: 1 x DVI-D; Analog: 1 x mini D-sub 15 pin
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Auto Adjust; Colour Temperature Control; Fine Adjust (analog); Brightness; Intelligent Power Management, Contrast; Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); sRGB; On-Screen-Manager (OSM) lock-out
Safety and Ergonomics	CE; Energy Star; FCC Class B; ISO 13406-2 (Pixel Failure Cass II); PCT Gost; TCO03; TÜV ERGONOMIE; TÜV GS; UL/C-UL or CSA; MPR II/ MPR II
Power Requirements on Mode [W]	52 (max.)
Power Requirements Power-saving Mode [W]	< 2
Power Supply	100-120 V/220-240 V; 0.95 A/0.55 A; integrated power supply
Ambient Temperature (operating) [°C]	5 to 35
Ambient Humidity (operating) [%]	30 to 80
VESA Mounting [mm]	100 x 100
ErgoDesign®: Height-adjustable Stand [mm]	75
Dimensions (B x H x T) [mm]	445 x 391 x 214
Screen Tilt / Swivel [°]	-5 to +30 / -175 to +175
Bezel Width [mm]	17.5
Cable Management	yes
Kensington Lock	yes
Weight [kg]	9.4
Specials	Rapid Response; NaViSet™ and NaViSet™ Administrator compatible; sRGB Support; Power Off Timer
Audio Functions	no
Colour Versions	Silver Front Bezel, Black Back Cabinet; Silver Front Bezel, Light Grey Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable VGA-VGA, Signal Cable DVI-D-DVI-D, CD-ROM; Sales Office List; Manual
Warranty	3 years warranty incl. backlight; 3 years on-site warranty within EU countries, Switzerland, Norway, Liechtenstein and Iceland; with optional exchange or repair and return service

TCO 03 DISPLAYS · CE · TÜV GS PRODUCT SERVICE · ERGONOMIE GEPRÜFT ERGONOMICS APPROVED · ISO 13406-2

sRGB · NaViSet™ · NaViSet™ Administrator · Energy

LCD2060NX-D-03/04

All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. March 2004